

Endosono Diameters & BN Angulation

Hersteller	Product	IT Diameter	Channel Diamter	Balloonchannel	Working Lengh	Angulation (°)		Angle of view	BN Rubbers	Bit max
		(mm)	(mm)	Diameter	(mm)	Up / Down	Right / Left	(°)	(ID mm)	(mm)
OLYMPUS	BF-UCT180 F	6,3	2,2		600	120 / 90		80	6,3	
	BF-UCT160F-OL8	6,2	2,0		890	120 / 90		80	6,3	
	GF-UCT 180	12,6	3,7		1250	130 / 90	90 / 90	55	12,2	
	GF-UE160-AL5	13,8	2,2		1250	130 / 90	90 / 90	55	11,2	
	GF-UC140P-AL5	11,8	2,8		1250	130 / 90	90 / 90	55	12,2	
	GF-UCT140-AL5	12,6	3,7		1250	130 / 90	90 / 90	55	12,2	
	GF-UCT240-AL5	12,6	3,7		1250	130 / 90	90 / 90	100	12,0	
	UC-160 F	6,3							5,6	
PENTAX	EB-1970UK	6,3	2,0	0,5	600	120 / 90		100	5,6	
	EG-3670URK	12,1	2,4	1,2	1250	130 / 60	60 / 60	140	11,2	13,5
	EG-3870UTK	12,8	3,8	1,2	1250	130 / 130	120 / 120	120	12,0	14,7
	EG-3270UK	10,8	2,8		1250	130 / 130	120 / 120	120	10,0	12,5
	FG-3870UX								12,0	
	EG-3630UR	12,1	2,4		1250	130 / 60	60 / 60		12,0	
	EG-3830UT	12,8	3,8		1250	130 / 130	120 / 120	120	12,0	
	FG-36UX	12,1	2,4		1250	130 / 130	120 / 120	105		
	FG38UX	12,8	3,2		1250	130 / 130	120 / 120	105	12,2	
	FI-16BS	5,1	2,6		600	160 / 130		95		
FUJINON	EB-530US	6,3	6,3		610	130 / 90		120		
	EG-530UR2	11,5	2,2		1250	180 / 90	100 / 100	140	11,0	
	EG-530UT2	12,1	3,8		1250	160 / 160	120 / 120	140		

